

Earth




army 14



beige 05



burgundy 34



plumb 168



shitake 124




cabernet 205



copper 126



forest 162



teal 198



wood 108



graphite 66



indigo 90



liver 10




slate 87



magnolia 160



mustard 06



onyx 169

Earth

Earth - Article passport


Knitted velvet made from 100% RPET bottles with a light shiny and elegant look.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

| | |
|----------------------|---|
| Productgroup | knitted velvet |
| Applications | sofa's, beds, chairs with fitted and loose fitting upholstery |
| Composition faceside | 100%RPET |
| Composition backside | n/a |
| Bonding / Coating | n/a |
| Statistic code | 60053900 |
| Dyeing method | piece dyed |
| Available colours | 17 |
| Packaging | boxes |

Durability specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
|-------------------------------------|--|-------------------------|--------|------------|-----|---------------------------|-----------------------|----------------------------|
| | | | | Dry | Wet | DGM | DGM+ | |
| Abrasion resistance - yarn breakage | DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03 | CTL | cycles | >100.000 | | min. 20.000 | min. 40.000 | A |
| Pilling | DIN EN ISO 12945-2:2000-11. 2000 cycles | CTL | grade | 4-5 | | min. 3-4 | min. 4 | A |
| Colour fastness to light | DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5 | | | | | | | |
| | light colours | CTL | grade | 5 | | min. 4 | min.5 | B |
| | middle colours | CTL | grade | 5 | | min. 4 | min.5 | B |
| Colour fastness to rubbing | DIN EN ISO 105-X12:2016-11 | | | | | | | |
| | light colours | CTL | grade | 5 | 5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A |
| | middle colours | CTL | grade | 4-5 | 5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A |
| Ignitability (cigarette test) | BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette | | | | | | | |
| |  | CTL | | passed | | | | |

Processing specifications

| Minimum workable width in centimeters | ± 138 | | | | | | | |
|---|---|-------------------------|--------|------------|------|---------------------------|----------|----------------------------|
| Roll length in meters | ± 35 | | | | | | | |
| Material weight in grams per linear meter | ± 620 | | | | | | | |
| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
| | | | | Warp | Weft | DGM | DGM+ | |
| Tensile strength | DIN EN ISO 13934-1:2013-08 | CTL | Newton | 631 | 982 | min. 350 | min. 400 | A/A |
| Tear growth resistance | DIN EN ISO 13937-3:2000-06 | CTL | Newton | 46,7 | 60,7 | min. 25 | min. 30 | A/A |
| Resistance to seam slippage | DIN EN ISO 13936-2:2004-07. Load 180 N | CTL | mm | 2,1 | 2,0 | max. 5 | max. 4 | A/A |
| Delamination | DIN 53530:1981-02 | CTL | Newton | n/a | n/a | n/a | n/a | n/a |
| Chemical substances | REACH | Centexbel | | passed | | | | |
| | Oeko-Tex, product class II | Centexbel | | certified | | | | |

Cleaning specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
|--|---|-------------------------|------|------------|------|---------------------------|------|----------------------------|
| | | | | Warp | Weft | DGM | DGM+ | |
| Dimensional change for washing 30 degrees celcius / air drying | DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08 | CTL | % | 0,0 | 0,0 | n/a | n/a | A/A |



- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture slightly damp after washing.
- Please note that during washing the damp- and dirt prevented treatment will disappear faster.
- Dirt and damp prevention treatment applied.

OEKO-TEX®
CERTIFIED BY

